

MATERIAL SAFETY DATA SHEET

HYDROFLUOSILICIC ACID, 20 - 30 %

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Brenntag Canada Inc.
43 Jutland Road.
Toronto, Ontario
M8Z 2G6
(416) 259-8231

WHMIS Number: 00060388
Index: GCD1379/06A
Effective Date: 2006 January 12
Date of Revision: 2006 January 12
Website: <http://www.brenntag.ca>

EMERGENCY TELEPHONE NUMBERS (FOR EMERGENCIES INVOLVING CHEMICAL SPILLS OR RELEASE)

Toronto, ON (416) 226-6117	Montreal, QC (514) 861-1211	Winnipeg, MB (204) 943-8827
Edmonton, AB (780) 424-1754	Calgary, AB (403) 263-8660	Vancouver, BC (604) 685-5036

PRODUCT IDENTIFICATION

Product Name: Hydrofluosilicic Acid 20 - 30 %.
Chemical Name: Hydrofluosilicic Acid.
Synonyms: Fluosilicic Acid; Hexafluosilicic Acid; Hydrogen Hexafluosilicate;
Hydrosilicofluoric Acid; Silicofluoric Acid; Silicon Hexafluoride Dihydride; Sand Acid;
Fluorosilicic Acid.
Chemical Family: Inorganic Acid.
Molecular Formula: H_2SiF_6 .
Product Use: Glass manufacturing. Chemical intermediate. Laboratory reagent.
CAS #: 16961-83-4.
WHMIS Classification / Symbol: D-1B: Toxic (acute effects), E: Corrosive.



READ THE ENTIRE MSDS FOR THE COMPLETE HAZARD EVALUATION OF THIS PRODUCT.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Corrosive! May be fatal if inhaled or swallowed. Causes severe skin and eye burns. Vapours are extremely irritating to eyes and respiratory tract. At elevated temperatures may cause irritation of the eyes and respiratory tract. High vapour concentrations may cause drowsiness. See "Other Health Effects" Section. Can decompose at high temperatures forming toxic gases. Contents may develop pressure on prolonged exposure to heat.

POTENTIAL HEALTH EFFECTS

- Inhalation: Corrosive! Product may cause severe irritation of the nose, throat and respiratory tract. Repeated and/or prolonged exposures may cause productive cough, running nose, bronchopneumonia, pulmonary oedema (fluid build-up in lungs), and reduction of pulmonary function. Mist or spray may be irritating to the nose, throat and respiratory tract. See "Other Health Effects" Section.
- Skin Contact: Corrosive! Burns can occur if not promptly removed. Concentrated solutions may cause pain and deep and severe burns to the skin. Prolonged and repeated exposure to dilute solutions often causes irritation, redness, pain and drying and cracking of the skin. Toxic effects may be delayed.

- . Skin Absorption: Skin absorption is a secondary concern to the continual destruction of tissue while the product is in contact with the skin.
 - . Eye Contact: Extremely corrosive! This product causes corneal scarring and clouding. Glaucoma, cataracts and permanent blindness may occur.
 - . Ingestion: Corrosive! This product causes severe burning and pain in the mouth, throat and abdomen. Vomiting, diarrhea and perforation of the esophagus and stomach lining may occur.
- Other Health Effects: Corrosive effects on the skin and eyes may be delayed, and damage may occur without the sensation or onset of pain. Strict adherence to first aid measures following any exposure is essential.

May cause pulmonary oedema, fluorosis, exostoses, hypocalcemia, shock, central nervous system (CNS) depression, coma and death. CNS depression is characterized by headache, dizziness, drowsiness, nausea, vomiting and incoordination. Severe overexposures may lead to coma and possible death due to respiratory failure. Pulmonary oedema is the build-up of fluid in the lungs that might be fatal. Symptoms of pulmonary oedema, such as shortness of breath, may not appear until several hours after exposure and are aggravated by physical exertion. (4)

Fluoride is a bone seeker, and excessive amounts will produce weakening and degeneration of the bone structure. Chronic exposure may cause excess accumulation of fluorine (fluorosis) in the teeth and bones. Severe fluorosis in children weakens tooth enamel resulting in surface pitting. After prolonged high intake in adults bony changes occur characterized by hardening or abnormal density of bone (osteosclerosis), benign bony growths projecting outward from the surface of the bone (exostoses) and calcification of ligaments, tendons, and muscle attachments to bone. Ingestion and skin contact may cause an abnormal reduction of blood calcium (hypocalcemia) and kidney damage since fluorides precipitate calcium stored in the body. There may also be heart, asthma, nerve, intestinal and rheumatism problems. (1,3,4)

3. COMPOSITION, INFORMATION ON INGREDIENTS (Not Intended As Specifications)

Hazardous Ingredients	CAS No.	ACGIH TLV	%
Hydrofluosilicic Acid	016961-83-4	2.5 mg/M3 As fluoride *A4	20 - 30

A4 = Not classifiable as a human carcinogen. (ACGIH-A4)

4. FIRST AID MEASURES

FIRST AID PROCEDURES

General Guidelines: Prompt removal of the material and obtaining medical attention are essential for all contact. Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water. Continue the flushing during transportation to the emergency department. Corrosive effects may be delayed (up to 72 hours), and damage may occur without the sensation or onset of pain. Contact local poison control centre for further guidance.

- . Inhalation: Move victim to fresh air. Give artificial respiration ONLY if breathing has stopped. Give cardiopulmonary resuscitation (CPR) if there is no breathing AND no pulse. Oxygen administration may be beneficial in this situation but should only be administered by personnel trained in its use. Obtain medical attention IMMEDIATELY.
- . Skin Contact: Prompt removal of the material from the skin is essential. Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. Obtain medical attention IMMEDIATELY.
- . Eye Contact: Immediately flush eyes with running water for a minimum of 30 minutes, preferably up to 60 minutes. Hold eyelids open during flushing. If irritation persists,

repeat flushing. Do not transport victim until the recommended flushing period is completed unless flushing can be continued during transport.

- . Ingestion: Do not attempt to give anything by mouth to an unconscious person. IMMEDIATELY contact local Poison Control Centre. If victim is alert and not convulsing, rinse mouth out and give 1 to 2 glasses of milk. Water may be used if milk is not available but it is not as effective. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomitus, rinse mouth and administer more milk or water. IMMEDIATELY transport victim to an emergency facility.

Note to Physicians: Immediate consultation with the local Poison Control Centre should be initiated. Severe and sometimes delayed (up to 72 hours) local and systemic reactions can occur.

Treatment for corrosive chemical contact with skin:

1. Immerse the exposed part immediately in ice water to relieve pain and to prevent swelling and blistering. Place cold packs, ice or wet cloths on the burned area if immersion is not possible.
2. Remove anything that is constrictive, such as rings, bracelets or footwear, before swelling begins.
3. Cover the exposed part with a clean, preferably sterile, lint-free dressing.
4. For severe exposure, immediately seek medical attention and monitor breathing and treat for shock.

Due to the severely irritating or corrosive nature of the material, swallowing may lead to ulceration and inflammation of the upper alimentary tract with hemorrhage and fluid loss. Also, perforation of the esophagus or stomach may occur, leading to mediastinitis or peritonitis and the resultant complications. (3)

Mucosal injury following ingestion of this corrosive material may contraindicate the induction of vomiting in the treatment of possible intoxication. Similarly, if gastric lavage is performed, intubation should be done with great care. If oral burns are present or a corrosive ingestion is suspected by the patient's history, perform esophagoscopy as soon as possible. Scope should not be passed beyond the first burn because of the risk of perforation.

This product contains materials that may cause severe pneumonitis if aspirated. If ingestion has occurred less than 2 hours earlier, carry out careful gastric lavage; use endotracheal cuff if available, to prevent aspiration. Observe patient for respiratory difficulty from aspiration pneumonitis. Give artificial resuscitation and appropriate chemotherapy if respiration is depressed.

Medical conditions that may be aggravated by exposure to this product include neurological, cardiovascular and skin disorders, diseases of the skin, eyes or respiratory tract.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

Flammability Class (WHMIS): Not regulated.
Flash Point (TCC, Deg. Celsius): Not available.
Autoignition Temperature (Deg. Celsius): Not available.
Flammability Limits in Air (%): LEL: Not available. UEL: Not available.

Hazardous Combustion Products: Thermal decomposition products are toxic and may include Hydrogen Fluoride, flammable hydrogen gas and silica tetrafluoride.

Unusual Fire or Explosion Hazards: Closed containers exposed to heat may explode. Reacts with many metals to form flammable and explosive hydrogen gas. Decomposition above 105 Deg. Celsius will produce toxic and corrosive vapours of fluorides.

Sensitivity to Mechanical Impact: Not expected to be sensitive to mechanical impact.
Rate of Burning: Not available.
Explosive Power: Not available.
Sensitivity to Static Discharge: Not expected to be sensitive to static discharge.

EXTINGUISHING MEDIA

Fire Extinguishing Media: Not normally a fire hazard. Water content of product prevents ignition. Use media appropriate for surrounding fire and/or materials.

FIRE FIGHTING INSTRUCTIONS

Instructions to the Fire Fighters: Fire-exposed containers should be kept cool by spraying with water to reduce pressure. Spilled material may cause floors and contact surfaces to become slippery.

Fire Fighting Protective Equipment: Use self-contained breathing apparatus and protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Information in this section is for responding to spills, leaks or releases in order to prevent or minimize the adverse effects on persons, property and the environment. There may be specific reporting requirements associated with spills, leaks or releases, which change from region to region.

Containment and Clean-Up Procedures: See Section 13, "Deactivating Chemicals".

Wear protective clothing. In all cases of leak or spill contact vendor at Emergency Number shown on the front page of this MSDS. Utilize a spill kit, if available. Spilled material may cause floors and contact surfaces to become slippery. Collect product for recovery or disposal. For release to land, or storm water runoff, contain discharge by constructing dykes or applying inert absorbent; for release to water, utilize damming and/or water diversion to minimize the spread of contamination. Ventilate enclosed spaces. Notify applicable government authority if release is reportable or could adversely affect the environment.

7. HANDLING AND STORAGE

HANDLING

Handling Practices: Use normal "good" industrial hygiene and housekeeping practices. Containers exposed to heat may be under internal pressure. These should be cooled and carefully vented before opening. A face shield and apron should be worn.

Ventilation Requirements: See Section 8, "Engineering Controls".

Other Precautions: Use only with adequate ventilation and avoid breathing aerosols (vapours or mists). Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Wash contaminated clothing thoroughly before re-use.

STORAGE

Storage Temperature (Deg Celsius): See below.

Ventilation Requirements: Ventilation should be corrosion proof.

Storage Requirements: Store in a clean, cool well ventilated area, away from organic chemicals, strong bases, strong acids, metal powders, carbides, sulfides, and any readily oxidizable material. Protect from direct sunlight. Protect against physical damage. Storage area should be equipped with acid-resistant floors, sumps and should have controlled drainage to a recovery tank. Storage tanks should be in a contained area to control any spills or leaks. Storage area should be equipped with corrosion-resistant floors, sumps and should have controlled drainage to a recovery tank.

Corrosive mist is most likely to be generated at the vents of process or storage tanks, especially during filling operations. The use of compressed air to force corrosive materials from delivery trucks is of special concern. Scrubbing the exhaust of these vents is highly recommended. Jurisdictional regulations should be consulted to determine required practices. Protect from direct sunlight. Protect against physical damage.

Special Materials to be Used for Packaging or Containers: Equipment for storage, handling or transportation should NOT be made of: metals, stoneware and glass. Confirm suitability of

any material before using.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Recommendations listed in this section indicate the type of equipment, which will provide protection against overexposure to this product. Conditions of use, adequacy of engineering or other control measures, and actual exposures will dictate the need for specific protective devices at your workplace.

ENGINEERING CONTROLS

Engineering Controls: Local exhaust ventilation required. Ventilation should be corrosion proof. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Ventilate low lying areas such as sumps or pits where dense vapours may collect.

For personnel entry into confined spaces (i.e. bulk storage tanks) a proper procedure must be followed. It must include consideration of, among other things, ventilation, testing of tank atmosphere, provision and maintenance of SCBA, and emergency rescue. Use the "buddy" system. The second person should be in view and trained and equipped to execute a rescue. (4)

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Eye Protection: Safety glasses with side shields are recommended to prevent eye contact. Use full face-shield and chemical safety goggles when there is potential for contact. Contact lenses should not be worn when working with this material.

Skin Protection: Gloves and protective clothing made from neoprene, butyl rubber, natural rubber, nitrile rubber or PVC should be impervious under conditions of use. Discard contaminated gloves. Prior to use, user should confirm impermeability.

Respiratory Protection: No specific guidelines available. A NIOSH/MSHA-approved full facepiece air-purifying respirator equipped with acid gas, dust, mist, fume cartridges for concentrations up to 20 ppm. (3) An air-supplied respirator if concentrations are higher or unknown.

If while wearing a respiratory protection, you can smell, taste or otherwise detect anything unusual, or in the case of a full facepiece respirator you experience eye irritation, leave the area immediately. Check to make sure the respirator to face seal is still good. If it is, replace the filter, cartridge or canister. If the seal is no longer good, you may need a new respirator. (4)

Other Personal Protective Equipment: Wear an impermeable apron and boots. Locate safety shower and eyewash station close to chemical handling area. Take all precautions to avoid personal contact.

EXPOSURE GUIDELINES

	ACGIH TLV (STEL)	OSHA PEL (TWA)	(STEL)	NIOSH REL (TWA)	(STEL)
Hydrofluosilicic Acid	----	2.5 mg/M3 as F	----	2.5 mg/m3 as F	----

9. PHYSICAL AND CHEMICAL PROPERTIES (Not intended as Specifications)

Physical State: Liquid.

Appearance and Odour: Water white to straw yellow, fuming liquid. Strong, pungent odour.

Odour Threshold (ppm): Not applicable.

Boiling Range (Deg Celsius): 105.

Melting/Freezing Point (Deg Celsius): -15.5.

Vapour Pressure (mm Hg at 20 Deg. Celsius): 24.

Vapour Density (Air = 1.0): Not available.

Relative Density (g/cc): 1.234 (25 % Aqueous Solution).

Bulk Density: 1,233 Kg/M3.
Viscosity: Not available.
Evaporation Rate (Butyl Acetate = 1.0): Not applicable.
Solubility: Soluble in water.
% Volatile by Volume: Not available.
pH: 1.2. (1 % Hydrofluosilicic Acid Aqueous Solution).
Coefficient of Water/Oil Distribution: Not available.
Volatile Organic Compounds (VOC): Not available.

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY

Under Normal Conditions: Stable.
Under Fire Conditions: Not flammable. Not a fire hazard. Water content of product prevents ignition.
Hazardous Polymerization: Will not occur.

Conditions to Avoid: High temperatures, sparks, open flames and all other sources of ignition.

Materials to Avoid: Strong oxidizers. Lewis or mineral acids. Alkalies. Stoneware. Glass. Combustibles. Strong bases. Metals. Alkali metals and their hydroxides. Silica will dissolve in hydrofluoric acid to produce a corrosive gas, silicon tetrafluoride.

Decomposition or Combustion Products: Thermal decomposition products are toxic and may include oxides of Hydrogen Fluoride, flammable hydrogen gas and silica tetrafluoride.

11. TOXICOLOGICAL INFORMATION

Toxicological Data:

Hydrofluosilicic Acid LD50 (Oral, Rat) = 430 mg/Kg (1)

Carcinogenicity Data: The ingredient(s) of this product is (are) not classed as carcinogenic by ACGIH, IARC, OSHA or NTP.
Reproductive Data: No adverse reproductive effects are anticipated.
Mutagenicity Data: No adverse mutagenic effects are anticipated.
Teratogenicity Data: No adverse teratogenic effects are anticipated.
Respiratory / Skin Sensitization Data: None known.
Synergistic Materials: None known.

Other Studies Relevant to Material:

Morphological changes in the skin of rats, guinea pigs and swine were studied after application of concentrated Hydrofluosilicic Acid. The intact skin was not affected by this acid. Areas injured before application of the acid showed a continuous spreading of necrosis in the deeper regions. The main characteristics findings were the hypodermis necrosis and edema reaching as far as the subcutis. The necrosis showed sharp leukocyte demarcations. (4)

12. ECOLOGICAL INFORMATION

Ecotoxicity: Not available. Harmful to aquatic life at low concentrations. Toxicity is primarily associated with pH.

Environmental Fate: Not available. Can be dangerous if allowed to enter drinking water intakes. Do not contaminate domestic or irrigation water supplies, lakes, streams, ponds, or rivers.

13. DISPOSAL CONSIDERATIONS

Deactivating Chemicals: Use calcium hydroxide (hydrated lime) to neutralize fluosilicic acid

to a pH between 7.0 and 9.0. The use of sodium hydroxide (caustic soda) and sodium carbonate (soda ash) is not acceptable because they contribute soluble fluoride containing salts to the environment. Calcium fluoride is not soluble and therefore is easy to contain, control and clean up. Calcium fluoride is also present in soils at levels of up to 2 %. Sodium fluoride (formed when sodium hydroxide or sodium carbonate is mixed with fluorides) is soluble and very toxic to animals and fish. Additionally, because of the solubility, sodium fluoride can spread into waterways and contaminate other areas of the environment. Neutralization is expected to be exothermic. Effervescence may result.

Waste Disposal Methods: This information applies to the material as manufactured. Reevaluation of the product may be required by the user at the time of disposal since the product uses, transformations, mixtures and processes may influence waste classification. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local, provincial and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

Safe Handling of Residues: See "Waste Disposal Methods".

Disposal of Packaging: Empty containers retain product residue (liquid and/or vapour) and can be dangerous. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. Do not dispose of package until thoroughly washed out. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local, provincial and federal regulations.

14. TRANSPORTATION INFORMATION

Please consult the North American Emergency Response Guidebook, via the UN#, for guidance in addressing spills.

CANADIAN TDG ACT SHIPPING DESCRIPTION:

Fluorosilicic Acid, Class 8, UN1778, Pk Gp II.
Label(s)/Placard(s): Corrosive. Exemptions: Not applicable.
ERAP Index: Not applicable.

US DOT CLASSIFICATION (49CFR 172.101, 172.102):

Fluorosilicic Acid, Class 8, UN1778, Pk Gp II.
Label(s)/Placard(s): Corrosive.
Reportable Quantity (CERCLA-RQ): Not applicable. Exemptions: Not applicable.

15. REGULATORY INFORMATION

CANADA

CEPA - NSNR: This material is included on the DSL under the CEPA.
CEPA - NPRI: Not included.
Controlled Products Regulations Classification (WHMIS): D-1B: Toxic (acute effects), E: Corrosive.

USA

Environmental Protection Act:
OSHA Hazard Communication (29CFR 1910.1200) Classification: Toxic, Corrosive.

HMIS: 3 Health, 0 Fire, 1 Reactivity. (3)

INTERNATIONAL: Hydrofluosilicic Acid: EINECS (European Inventory of Existing Commercial Chemical Substances).

16. OTHER INFORMATION

ADDITIONAL INFORMATION AND SOURCES USED

1. RTECS-Registry of Toxic Effects of Chemical Substances, Canadian Centre for Occupational Health and Safety RTECS database.
2. Clayton, G.D. and Clayton, F.E., Eds., Patty's Industrial Hygiene and Toxicology, 3rd ed., Vol. IIA,B,C, John Wiley and Sons, New York, 1981.

3. Supplier's Material Safety Data Sheet(s).
 4. "CHEMINFO", through "CCINFODisc", Canadian Centre for Occupational Health and Safety, Hamilton, Ontario, Canada.
 5. Guide to Occupational Exposure Values, 2005, American Conference of Governmental Industrial Hygienists, Cincinnati, 2005.
 6. The British Columbia Drug and Poison Information Centre, Poison Managements Manual, Canadian Pharmaceutical Association, Ottawa, 1981.
-

The information contained herein is offered only as a guide to the handling of this specific material and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive and the manner and conditions of use and handling may involve other and additional considerations. No warranty of any kind is given or implied and Brenntag Canada Inc. will not be liable for any damages, losses, injuries or consequential damages which may result from the use of or reliance on any information contained herein. This Material Safety Data Sheet is valid for three years.

To obtain revised copies of this or other Material Safety Data Sheets, contact your nearest Brenntag Canada Regional office.

British Columbia: 20333-102B Avenue, Langley, BC, V1M 3H1
Phone: (604) 513-9009 Facsimile: (604) 513-9010

Alberta: 6628 - 45 th. Street, Leduc, AB, T9E 7C9
Phone: (780) 986-4544 Facsimile: (780) 986-1070

Manitoba: 681 Plinquet Street, Winnipeg, MB, R2J 2X2
Phone: (204) 233-3416 Facsimile: (204) 233-7005

Ontario: 43 Jutland Road, Toronto, ON, M8Z 2G6
Phone: (416) 259-8231 Facsimile: (416) 259-6175

Quebec: 2900 Jean Baptiste Des., Lachine, PQ, H8T 1C8
Phone: (514) 636-9230 Facsimile: (514) 636-0877

Atlantic: A-105 Akerley Boulevard, Dartmouth, NS, B3B 1R7
Phone: (902) 468-9690 Facsimile: (902) 468-3085

Prepared By: Regulatory Affairs Group, Brenntag Canada Inc., (416) 259-8231.